



ALL DIMENSIONS ARE IN MILLIMETERS (mm) EXCEPT AS NOTED.

GENERAL NOTES : EARTH MOUND TO BE SEEDED WHERE TOTAL DEPTH OF EARTH EXCEEDS 450 mm ELSEWHERE, EARTH MOUND SHALL BE COVERED WITH WOOD-CHIP MULCH.

THESE DIAGRAMS REPRESENT FILL CONDITIONS ONLY. CUT CONDITIONS SHALL BE SUBJECT TO THE DESIGNER'S DISCRETION TO MEET ACTUAL CONDITIONS. DRAINAGE SHALL BE DESIGNED AS REQUIRED TO MEET FIELD CONDITIONS.

1:1 FLATTER SLOPE IS PREFERRED AND SHALL BE USED WHERE SITE CONDITIONS ALLOW. 1:6 SLOPE IS DESIRABLE.

1:2 APPROACH SHOULDER WIDTH.

1:4 10 mm DENSE GRADED BITUMINOUS CONCRETE (ONLY REQUIRED OVER CONC. PAVT.)

1:4 WHEN INTERCHANGE IS OPEN TO TRAFFIC. REMOVE 10 mm DENSE GRADED BITUMINOUS CONCRETE, BITUMINOUS CONCRETE LIP CURBING AND EARTH MOUND.

TYPICAL TEMPORARY EARTH MOUND BARRICADE